

CARNEGIE MELLON UNIVERSITY
COMPUTER SCIENCE DEPARTMENT
15-445/645 – DATABASE SYSTEMS (FALL 2025)
PROF. ANDY PAVLO

Homework #6 (by Will)
Due: **Sunday December 7, 2025 @ 11:59pm**

IMPORTANT:

- Enter all of your answers into **Gradescope by 11:59pm on Sunday December 7, 2025**.
- **Plagiarism:** Homework may be discussed with other students, but all homework is to be completed **individually**.
- **You have to use this PDF for all of your answers.**

For your information:

- Graded out of **100** points; **3** questions total
- Each part is all or nothing. There is no partial credit.

Revision : 2025/12/01 15:08

Question	Points	Score
ARIES	48	
Logging and Recovery	32	
Distributed Databases	20	
Total:	100	

Question 1: ARIES [48 points]

Consider the sequence of ARIES undo/redo log records with fuzzy checkpointing in Figure 1. The transaction ids are T1, T2, T3, and T4. The object ids are A, B, C, D, and E. Each object is stored in a separate page, and the page id for an object is the same as its object id.

Reminder: Recall the following information about the ARIES log record format:

- The number at the start of each log record indicates the log sequence number (LSN).
- Each record for a transaction write includes the LSN, the transaction id, the log record type, and the previous LSN.
- For updates, the record also includes the object id, the before-image (former value) of the object and the after-image (new value) of the object, in that order.
- Compensation log records contain the same information as update records and also the undoNextLSN (i.e., the next LSN that needs to be undone).

LSN	RECORD
1000	<T1, BEGIN, prevLSN=∅>
1001	<T2, BEGIN, prevLSN=∅>
1002	<T3, BEGIN, prevLSN=∅>
1003	<T1, UPDATE, prevLSN=1000, A, 1, 2>
1004	<T3, UPDATE, prevLSN=1002, C, 1, 2>
1005	<T3, COMMIT, prevLSN=1004 >
1006	< CHECKPOINT-BEGIN >
1007	<T1, UPDATE, prevLSN=1003, B, 1, 2>
1008	<T4, BEGIN, prevLSN=∅>
1009	<T4, UPDATE, prevLSN=1008, C, 2, 3>
1010	< CHECKPOINT-END , DPT={C}, ATT={??}>
1011	<T2, UPDATE, prevLSN=1001, D, 1, 2>
1012	<T4, UPDATE, prevLSN=1009, E, 1, 2>
1013	<T3, TXN-END, prevLSN=1005 >
1014	< CHECKPOINT-BEGIN >
1015	<T1, UPDATE, prevLSN=1007, A, 2, 3>
1016	<T4, UPDATE, prevLSN=1012, E, 2, 3>
1017	< CHECKPOINT-END , DPT={??}, ATT={??}>
1018	<T1, UPDATE, prevLSN=1015, A, 3, 4>
1019	<T4, ABORT, prevLSN=1016 >
1020	< CHECKPOINT-BEGIN >
1021	<T1, COMMIT, prevLSN=1018 >
1022	<T4, CLR, prevLSN=1019, E, 3, 2, undoNextLSN=1012 >
1023	<T1, TXN-END, prevLSN=1021 >
	CRASH!

Figure 1: ARIES Write-Ahead Log

(a) Suppose the database started with a clean state (no active transactions and no dirty pages) at the start of the log, a background thread periodically flushes dirty buffer pool pages to reduce eviction and recovery costs, and a crash occurs after the log record 1010 is flushed to disk.

- [4 points] For **A**, which states are possibly stored on disk before recovery starts?
 A=1 A=2 A=3 Cannot be determined
- [4 points] For **B**, which states are possibly stored on disk before recovery starts?
 B=1 B=2 Cannot be determined
- [4 points] For **C**, which states are possibly stored on disk before recovery starts?
 C=1 C=2 C=3 Cannot be determined
- [4 points] Select the transactions that would be in the ATT at 1010.
 T1 T2 T3 T4 Cannot be determined

(b) Suppose the database started with a clean state (no active transactions and no dirty pages) at the start of the log, a background thread periodically flushes dirty buffer pool pages to reduce eviction and recovery costs, and a crash occurs after the log record 1017 is flushed to disk.

- [4 points] Select the transactions that would be in the ATT at 1017.
 T1 T2 T3 T4 Cannot be determined
- [6 points] Select all possible values of DPT at 1017.
 A B C D E B, C C, D D, E
 A, B, C B, C, D C, D, E
 A, B, C, D A, C, D, E B, C, D, E
 A, B, C, D, E Empty

(c) Suppose the database started with a clean state (no active transactions and no dirty pages) at the start of the log, a background thread periodically flushes dirty buffer pool pages to reduce eviction and recovery costs, and a crash occurs after the log record 1023 is flushed to disk. Assume that at 1017, the DPT is **Empty**.

- [2 points] Which LSN should be recorded in the DBMS's *MasterRecord*, which records the first LSN to be analyzed for recovery?
 1006 1010 1014 1017 1020 None of the above
- [2 points] Which pages are *definitely not dirty* at the time the last WAL record was written?
 A B C D E None of the above
- [2 points] Which pages are *definitely dirty* at the time the database crashed? Select all correct answers.
 A B C D E None of the above
- [2 points] Which pages are *maybe dirty* at the time the database crashed? Select all correct answers.
 A B C D E None of the above
- [2 points] Which log records will *definitely be redone* during the ARIES **REDO** phase? Select all correct answers.

1003 1004 1007 1009 1011 1012 1015
 1016 1018 1022 None of the above

vi. **[2 points]** Which log records will *definitely not be redone* during the ARIES **REDO** phase? Select all correct answers.

1003 1004 1007 1009 1011 1012 1015
 1016 1018 1022 None of the above

vii. **[2 points]** Which log records will *maybe be redone* during the ARIES **REDO** phase? Select all correct answers.

1003 1004 1007 1009 1011 1012 1015
 1016 1018 1022 None of the above

viii. **[4 points]** Which transactions will be undone in the **UNDO** phase of ARIES? Select all correct answers.

T1 T2 T3 T4 None of the above

ix. **[1 point]** For Transaction **T1**, how many new CLR entries will the DBMS add to the WAL during ARIES recovery for each transaction? Do not count any CLR entries that already exist in the WAL before the crash in your answer. 0 1 2
 3

x. **[1 point]** For Transaction **T2**, how many new CLR entries will the DBMS add to the WAL during ARIES recovery for each transaction? Do not count any CLR entries that already exist in the WAL before the crash in your answer. 0 1 2
 3

xi. **[1 point]** For Transaction **T3**, how many new CLR entries will the DBMS add to the WAL during ARIES recovery for each transaction? Do not count any CLR entries that already exist in the WAL before the crash in your answer. 0 1 2
 3

xii. **[1 point]** For Transaction **T4**, how many new CLR entries will the DBMS add to the WAL during ARIES recovery for each transaction? Do not count any CLR entries that already exist in the WAL before the crash in your answer. 0 1 2
 3

Question 2: Logging and Recovery [32 points]

(a) **[4 points]** The STEAL policy means that the pages modified by a transaction *could* be written to non-volatile storage before that transaction commits.

True
 False

(b) **[4 points]** In reference to recovery algorithms that use a write-ahead log (WAL). Under NO-STEAL + FORCE policy, a DBMS will have to undo the changes of an aborted transaction during recovery.

True
 False

(c) **[4 points]** If the DBMS is using the STEAL and NO-FORCE policies, then a transaction is considered committed if all of the data pages that it modified have been written to non-volatile storage.

True
 False

(d) **[4 points]** If the DBMS uses the FORCE policy, it could potentially have to redo the changes of previously committed transactions during recovery.

True
 False

(e) **[4 points]** In ARIES, only transactions that commit will have an associated “TXN-END” record in the log.

True
 False

(f) **[4 points]** Fuzzy checkpoints do not need to block the execution of all transactions while a consistent snapshot is written to disk.

True
 False

(g) **[4 points]** After the DBMS begins a non-blocking (i.e., fuzzy) checkpoint, the DBMS cannot flush dirty pages to disk until the checkpoint ends to ensure correctness.

True
 False

(h) **[4 points]** If the DBMS uses a *physical logging* scheme for its WAL, then it does not need to maintain additional WAL records for updates to indexes.

True
 False

Question 3: Distributed Databases [20 points]

(a) Consider a database that has a two tables $R(a, b, c)$ $S(a, d, e)$, where $S.a$ is a foreign key reference to $R.a$. Assume that R contains 100,000,000 tuples and S contains 1,000,000 tuples. Also assume that the size of a tuple in R is the same as a tuple in S .

Consider the following query:

```
SELECT * FROM R JOIN S ON R.a = S.a
WHERE R.b BETWEEN 1 AND 100;
```

Answer the following questions about the best way to execute this query given the different configurations in a distributed, shared-nothing DBMS with 10 nodes. You can assume that the DBMS executes a local hash join at each node. You can also assume that it is 10× faster for a node to read data from its local disk than it is to retrieve data from another node over the network. If a table is partitioned, then you can assume that each partition contains the same number of tuples (i.e., the data is not skewed).

Consider the following database configuration:

- Table R is partitioned on $R.a$. Each partition fits in memory on a single node.
- Table S is replicated at every node. The entire table fits in memory on a single node.

- [4 points]** What is the most optimal join execution strategy for table R ?
 - Leave R as it exists on every node.
 - Shuffle R on $R.a$ to every node.
 - Shuffle R on $R.b$ to every node.
 - Broadcast R to every node.
 - None of the above
- [4 points]** Given your choice for R , what is the most optimal join execution strategy for table S ?
 - Leave S as it exists on every node.
 - Shuffle S on $S.a$ to every node.
 - Shuffle S on $S.d$ to every node.
 - Broadcast S to every node.
 - None of the above

(b) **[4 points]** A distributed DBMS can immediately commit a transaction under network partitioning without any loss of data consistency.

True
 False

(c) **[4 points]** A DBMS can use either the PAXOS or Two-Phase Commit protocols to support strong consistency for distributed transactions (i.e., transactions that modify data on multiple nodes).

True
 False

(d) **[4 points]** With consistent hashing, if a node fails, then only a subset and not all keys will be reshuffled among the remaining nodes.

True
 False