

Carnegie Mellon University

Database Systems

15-445/645 SPRING 2026

ANDY PAVLO

JIGNESH PATEL

Lecture #10

Index Concurrency Control



ADMINISTRIVIA



Homework #3 is due Sunday Feb 22nd @ 11:59pm

Mid-Term Exam is on Wednesday Feb 25th @ 2:00pm

→ Lectures #01–11 (inclusive)

→ Study guide will be released later today.

UPCOMING DATABASE TALKS



TopK (DB Seminar)

→ Monday Feb 16th @ 4:30pm ET

→ Zoom



Microsoft HorizonDB (DB Seminar)

→ Monday Feb 23rd @ 4:30pm ET

→ Zoom



Chronon (DB Meeting)

→ Tuesday Feb 24th @ 12:00pm ET

→ GHC 9115



OBSERVATION

We (mostly) assumed all the data structures that we have discussed so far are single-worker.

→ Worker = Execution Context (i.e., Thread, Process)

A DBMS needs to allow multiple worker to safely access data structures to take advantage of additional CPU cores and hide disk I/O stalls.

OBSERVATION

We (mostly) assumed all the data structures that we have discussed so far are single-worker.

→ Worker = Execution Context (i.e., Thread, Process)

A DBMS needs to allow multiple worker to safely access data structures to take advantage of additional CPU cores and hide disk I/O stalls.



They Don't Do This!

CONCURRENCY CONTROL



A concurrency control protocol is the method that the DBMS uses to ensure "correct" results for concurrent operations on a shared object.

A protocol's correctness criteria can vary:

- **Logical Correctness:** Can a worker see the data that it is supposed to see?
- **Physical Correctness:** Is the internal representation of the object valid?

TODAY'S AGENDA

Latches Overview

Hash Table Latching

B+Tree Latching

Leaf Node Scans

Project #2 Announcement



LOCKS VS. LATCHES



Locks (Transactions)

- Protect the database's logical contents from other transactions.
- Held for transaction's duration.
- Application is not responsible for rolling back changes.

Latches (Workers)

- Protect the critical sections of the DBMS's internal data structure from other workers.
- Held for operation duration.
- Workers are responsible for rolling back changes.

LOCKS VS. LATCHES

	<i>Locks</i>	<i>Latches</i>
Separate...	Transactions	Workers (threads, processes)
Protect...	Database Contents	In-Memory Data Structures
During...	Entire Transactions	Critical Sections
Modes...	Shared, Exclusive, Update, Intention	Read, Write
Deadlock	Detection & Resolution	Avoidance
...by...	Waits-for, Timeout, Aborts	Coding Discipline
Kept in...	Lock Manager	Protected Data Structure

LOCKS VS. LATCHES



Lecture #15



Locks

Separate...	Transactions
Protect...	Database Contents
During...	Entire Transactions
Modes...	Shared, Exclusive, Update, Intention
Deadlock	Detection & Resolution
...by...	Waits-for, Timeout, Aborts
Kept in...	Lock Manager

Latches

Workers (threads, processes)
In-Memory Data Structures
Critical Sections
Read, Write
Avoidance
Coding Discipline
Protected Data Structure

LATCH MODES

Read Mode

- Multiple threads can read the same object at the same time.
- A thread can acquire the read latch if another thread has it in read mode.

Write Mode

- Only one thread can access the object.
- A thread cannot acquire a write latch if another thread has it in any mode.

Compatibility Matrix

	Read	Write
Read	✓	X
Write	X	X

LATCH IMPLEMENTATION GOALS

Small memory footprint.

Fast execution path when no contention.

Decentralized management of latches.

Avoid expensive system calls.

LATCH IMPLEMENTATION GOALS

Small memory footprint
 Fast execution path
 Decentralized management
 Avoid expensive operations

By: **Linus Torvalds** (torvalds.delete@this.linux-foundation.org), January 3, 2020 6:05 pm

Room: [Moderated Discussions](#)

Beastian (no.email.delete@this.aol.com) on January 3, 2020 11:46 am wrote:
 > I'm usually on the other side of these primitives when I write code as a consumer of them,
 > but it's very interesting to read about the nuances related to their implementations:

The whole post seems to be just wrong, and is measuring something completely different than what the author thinks and claims it is measuring.

First off, spinlocks can only be used if you actually know you're not being scheduled while using them. But the blog post author seems to be implementing his own spinlocks in user space with no regard for whether the lock user might be scheduled or not. And the code used for the claimed "lock not held" timing is complete garbage.

It basically reads the time before releasing the lock, and then it reads it after acquiring the lock again, and claims that the time difference is the time when no lock was held. Which is just inane and pointless and completely wrong.

That's pure garbage. What happens is that

- (a) since you're spinning, you're using CPU time
- (b) at a random time, the scheduler will schedule you out
- (c) that random time might be just after you read the "current time", but before you actually released the spinlock.

So now you still hold the lock, but you got scheduled away from the CPU, because you had used up your time slice. The "current time" you read is basically now stale, and has nothing to do with the (future) time when you are *actually* going to release the lock.

Somebody else comes in and wants that "spinlock", and that somebody will now spin for a long while, since nobody is releasing it - it's still held by that other thread entirely that was just scheduled out. At some point, the scheduler says "ok, now you've used your time slice", and schedules the original thread, and *now* the lock is actually released. Then another thread comes in, gets the lock again, and then it looks at the time and says "oh, a long time passed without the lock being held at all".

And notice how the above is the *good* schenario. If you have more threads than CPU's (maybe because of other processes unrelated to your own test load), maybe the next thread that gets scheduled isn't the one that is going to release the lock. No, that one already got its timeslice, so the next thread scheduled might be *another* thread that wants that lock that is still being held by the thread that isn't even running right now!

So the code in question is pure garbage. You can't do spinlocks like that. Or rather, you very much can do them like that, and when you do that you are measuring random latencies and getting nonsensical values, because what you are measuring is "I have a lot of busywork, where all the processes are CPU-bound, and I'm measuring random points of how long the scheduler kept the process in place".

And then you write a blog-post blaming others, not understanding that it's your incorrect code that is garbage, and is giving random garbage values.

LATCH IMPLEMENTATION GOALS

Small memory footprint
 Fast execution path
 Decentralized management
 Avoid expensive operations

By: **Linus Torvalds** (torvalds.delete@this.linux-foundation.org), January 3, 2020 6:05 pm

Room: [Moderated Discussions](#)

Beastian (no.email.delete@this.aol.com) on January 3, 2020 11:46 am wrote:
 > I'm usually on the other side of these primitives when I write code as a consumer of them,
 > but it's very interesting to read about the nuances related to their implementations:

The whole post seems to be just wrong, and is measuring something completely different than what the author thinks and claims it is measuring.

First off, spinlocks can only be used if you actually know you're not being scheduled while using them. But the blog post author seems to be implementing his own spinlocks in user space with no regard for whether the lock user might be scheduled or not. And the code used for the claimed "lock not held" timing is complete garbage.

It basically reads the time before releasing the lock, and then it reads it after acquiring the lock again, and claims that the time difference is the time when no lock was held. Which is just inane and pointless and completely wrong.

That's pure garbage. What happens is that

- (a) since you're spinning, you're using CPU time
- (b) at a random time, the scheduler will schedule you out
- (c) that random time might be just after you've

I repeat: **do not use spinlocks in user space, unless you actually know what you're doing.** And be aware that the likelihood that you know what you are doing is basically nil.

And then you write a blog-post blaming others, not understanding that it's your incorrect code that is garbage, and is giving random garbage values.

LATCH IMPLEMENTATIONS

Test-and-Set Spinlock

Blocking OS Mutex

Reader-Writer Locks

Advanced approaches:

- Adaptive Spinlock ([Apple ParkingLot](#))
- Queue-based Spinlock ([MCS Locks](#))
- Optimistic Lock Coupling ([The Germans](#))
- Cache-Friendly Queues ([Google nsync](#))

LATCH IM



Locking in WebKit

May 6, 2016 by Filip Pizlo @filpizlo

Back in August 2015 we replaced all spinlocks and OS-provided mutexes in WebKit with the new WTF::Lock (WTF stands for Web Template Framework). We also replaced all OS-provided condition variables with WTF::Condition. These new primitives have some cool properties:

1. WTF::Lock and WTF::Condition only require one byte of storage each. WTF::Lock only needs two bits in that byte. The small size encourages using huge numbers of very fine-grained locks. OS mutexes often require 64 bytes or more. The small size of WTF::Lock means that there's rarely an excuse for not having one, or even multiple, fine-grained locks in any object that has things that need to be synchronized.
2. WTF::Lock is super fast in the case that matters most: uncontended lock acquisition. Parallel lock acquisition is that a mature lock() when y, reads are intended and the lock will

- Test-and-Set Spinlock
- Blocking OS Mutex
- Reader-Writer Locks
- Advanced approaches

Compared to OS-provided locks like pthread_mutex, WTF::Lock is 64 times smaller and up to 180 times faster. Compared to OS-provided condition variables like pthread_cond, WTF::Condition is 64 times smaller. Using WTF::Lock instead of pthread_mutex means that WebKit is 10% faster on JetStream, 5% faster on Speedometer, and 5% faster on our page loading test.

3. This is the most common kind of contention in parallel code, since it's common to go to great pains to do very little work while holding a lock.
4. WTF::Lock doesn't waste CPU cycles when a lock is held for a long time. WTF::Lock is adaptive: it changes its strategy for how to wait for the lock to become available based on how long it has been trying. If the lock doesn't become available promptly, WTF::Lock will suspend the calling thread until the lock becomes available.


LATCH IMPLEMENTATIONS

Approach #1: Test-and-Set Spin Latch (TAS)

- Very efficient (single instruction to latch/unlatch)
- Non-scalable, not cache friendly, not OS friendly.
- Example: `std::atomic<T>`

std::atomic<bool>

```
std::atomic_flag latch;  
:  
while (latch.test_and_set()) {  
    // Retry? Yield? Abort?  
}
```




COMPARE-AND-SWAP

Atomic instruction that compares contents of a memory location **M** to a given value **V**

→ If values are equal, installs new given value **V'** in **M**

→ Otherwise, operation fails

See [C++11 Atomics](#)




COMPARE-AND-SWAP

Atomic instruction that compares contents of a memory location **M** to a given value **V**

→ If values are equal, installs new given value **V'** in **M**

→ Otherwise, operation fails

See [C++11 Atomics](#)




COMPARE-AND-SWAP

Atomic instruction that compares contents of a memory location **M** to a given value **V**

→ If values are equal, installs new given value **V'** in **M**

→ Otherwise, operation fails

See [C++11 Atomics](#)




LATCH IMPLEMENTATIONS

Approach #2: Blocking OS Mutex

- Simple to use
- Non-scalable (about 25ns per lock/unlock invocation)
- Example: `std::mutex` → `pthread_mutex_t` → `futex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```




LATCH IMPLEMENTATIONS

Approach #2: Blocking OS Mutex

- Simple to use
- Non-scalable (about 25ns per lock/unlock invocation)
- Example: `std::mutex` → `pthread_mutex_t` → `futex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```



LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

→ Allows for concurrent readers. Must manage read/write queues to avoid starvation.

→ Can be implemented on top of spinlocks.

→ Example: `std::shared_mutex` → `pthread_rwlock_t`




LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`




LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`



LATCH IMPLEMENTATIONS


Approach #3: Reader-Writer Latches

→ Allows for concurrent readers. Must manage read/write queues to avoid starvation.

→ Can be implemented on top of spinlocks.

→ Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`




LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`




LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`




LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`




LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`




LATCH IMPLEMENTATIONS

Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`
→ `pthread_cond_t`



HASH TABLE LATCHING

Easy to support concurrent access due to the limited ways workers access the data structure.

- All workers move in the same direction and only access a single page/slot at a time.
- Deadlocks are not possible.

To resize the table, take a global write latch on the entire table (e.g., in the header page).

HASH TABLE LATCHING

Approach #1: Global Latch

→ Use a single latch to protect the entire data structure.

Approach #2: Page/Block Latches

→ Each page/block has an embedded reader-writer latch.

→ Workers acquire latch before accessing a page/block.

→ Release latch before moving to the next page/block.


Approach #3: Slot Latches

→ Each slot has its own latch.

→ Can use a single-mode latch to reduce meta-data and computational overhead.


HASH TABLE: PAGE/BLOCK LATCHES

T_1 : Find D
 $hash(D)$




HASH TABLE: PAGE/BLOCK LATCHES

T_1 : Find D
 $hash(D)$




HASH TABLE: PAGE/BLOCK LATCHES

T_1 : Find D
 $hash(D)$



HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES

T_1 : Find D
 $hash(D)$




T_2 : Insert E
 $hash(E)$




HASH TABLE: PAGE/BLOCK LATCHES

T_1 : Find D
 $hash(D)$




T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES



HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: PAGE/BLOCK LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: SLOT LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: SLOT LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: SLOT LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: SLOT LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: SLOT LATCHES


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

HASH TABLE: SLOT LATCHES

T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)

HASH TABLE: SLOT LATCHES

T_1 : Find D

$hash(D)$

It's safe to release the latch on A




T_2 : Insert E

$hash(E)$

HASH TABLE: SLOT LATCHES


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

HASH TABLE: SLOT LATCHES


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

HASH TABLE: SLOT LATCHES

T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)

HASH TABLE: SLOT LATCHES


T_1 : Find D
hash(D)

T_2 : Insert E
hash(E)



HASH TABLE: SLOT LATCHES

T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)

HASH TABLE: SLOT LATCHES


T_1 : Find D
hash(D)

T_2 : Insert E
hash(E)



HASH TABLE: SLOT LATCHES

T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

B+TREE CONCURRENCY CONTROL


We want to allow multiple workers to read and update a B+Tree at the same time.

We need to protect against two types of problems:

- Workers modifying the contents of a node at the same time.
- One worker traversing the tree while another worker splits/merges nodes.


B+TREE MULTI-THREADED EXAMPLE

T_1 : Delete 44




B+TREE MULTI-THREADED EXAMPLE

T_1 : Delete 44




B+TREE MULTI-THREADED EXAMPLE

T_1 : Delete 44




B+TREE MULTI-THREADED EXAMPLE

T_1 : Delete 44




B+TREE MULTI-THREADED EXAMPLE

T_1 : Delete 44




B+TREE MULTI-THREADED EXAMPLE


T_1 : Delete 44




B+TREE MULTI-THREADED EXAMPLE




B+TREE MULTI-THREADED EXAMPLE




B+TREE MULTI-THREADED EXAMPLE




B+TREE MULTI-THREADED EXAMPLE




B+TREE MULTI-THREADED EXAMPLE



B+TREE MULTI-THREADED EXAMPLE



B+TREE MULTI-THREADED EXAMPLE



LATCH CRABBING/COUPLING

Protocol to allow multiple workers to access/modify B+Tree at the same time.

- Get latch for parent
- Get latch for child
- Release latch for parent if “safe”

A **safe node** is one that will not split or merge when updated.

- Not full (on insertion)
- More than half-full (on deletion)

LATCH CRABBING/COUPLING


Find: Start at root and traverse down the tree:

- Acquire **R** latch on child,
- Then unlatch parent.
- Repeat until we reach the leaf node.


Insert/Delete: Start at root and go down, obtaining **W** latches as needed. Once a child node is latched, check if it is safe:

- If child is safe, release all latches on ancestors.
- Optimization: When at an inner node that is “safe” can release all latches on ancestors.

EXAMPLE #1: FIND 38




EXAMPLE #1: FIND 38




EXAMPLE #1: FIND 38

T_1 : Find 38




EXAMPLE #1: FIND 38

T_1 : Find 38




EXAMPLE #1: FIND 38

T_1 : Find 38




EXAMPLE #1: FIND 38

T_1 : Find 38




EXAMPLE #1: FIND 38


T_1 : Find 38




EXAMPLE #2: DELETE 38




EXAMPLE #2: DELETE 38



EXAMPLE #2: DELETE 38




EXAMPLE #2: DELETE 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38


T_1 : Delete 38



EXAMPLE #3: INSERT 45




EXAMPLE #3: INSERT 45




EXAMPLE #3: INSERT 45

T_1 : Insert 45



EXAMPLE #3: INSERT 45


T_1 : Insert 45



Node I will not split, so we can release B+D.


EXAMPLE #3: INSERT 45

T_1 : Insert 45




EXAMPLE #3: INSERT 45

T_1 : Insert 45




EXAMPLE #3: INSERT 45

T_1 : Insert 45




EXAMPLE #4: INSERT 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25




EXAMPLE #4: INSERT 25

T_1 : Insert 25






EXAMPLE #4: INSERT 25

T_1 : Insert 25



OBSERVATION

What was the first step that all the update examples did on the B+Tree?



Taking a write latch on the root every time becomes a bottleneck with higher concurrency.

BETTER LATCHING ALGORITHM

Most modifications to a B+Tree will not require a split or merge.

Instead of assuming there will be a split/merge, optimistically traverse the tree using read latches.

If a worker guesses wrong, repeat traversal with pessimistic algorithm.

Acta Informatica 9, 1-21 (1977)



Concurrency of Operations on B-Trees

R. Bayer* and M. Schkolnick
IBM Research Laboratory, San José, CA 95193, USA

Summary. Concurrent operations on *B*-trees pose the problem of insuring that each operation can be carried out without interfering with other operations being performed simultaneously by other users. This problem can become critical if these structures are being used to support access paths, like indexes, to data base systems. In this case, serializing access to one of these indexes can create an unacceptable bottleneck for the entire system. Thus, there is a need for locking protocols that can assure integrity for each access while at the same time providing a maximum possible degree of concurrency. Another feature required from these protocols is that they be deadlock free, since the cost to resolve a deadlock may be high.

Recently, there has been some questioning on whether *B*-tree structures can support concurrent operations. In this paper, we examine the problem of concurrent access to *B*-trees. We present a deadlock free solution which can be tuned to specific requirements. An analysis is presented which allows the selection of parameters so as to satisfy these requirements.

The solution presented here uses simple locking protocols. Thus, we conclude that *B*-trees can be used advantageously in a multi-user environment.

1. Introduction

In this paper, we examine the problem of concurrent access to indexes which are maintained as *B*-trees. This type of organization was introduced by Bayer and McCreight [2] and some variants of it appear in Knuth [10] and Wedekind [13]. Performance studies of it were restricted to the single user environment. Recently, these structures have been examined for possible use in a multi-user (concurrent) environment. Some initial studies have been made about the feasibility of their use in this type of situation [1, 6], and [11].

An accessing schema which achieves a high degree of concurrency in using the index will be presented. The schema allows dynamic tuning to adapt its performance to the profile of the current set of users. Another property of the

* Permanent address: Institut für Informatik der Technischen Universität München, Arcisstr. 21, D-8000 München 2, Germany (Fed. Rep.)

BETTER LATCHING ALGORITHM


Search: Same as before.

Insert/Delete:

- Set latches as if for search, get to leaf, and set **W** latch on leaf.
- If leaf is not safe, release all latches, and restart thread using previous insert/delete protocol with write latches.


This approach optimistically assumes that only leaf node will be modified; if not, **R** latches set on the first pass to leaf are wasteful.

EXAMPLE #2: DELETE 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #2: DELETE 38

T_1 : Delete 38




EXAMPLE #4: INSERT 25

T_1 : Insert 25



EXAMPLE #4: INSERT 25

T_1 : Insert 25



OBSERVATION


The workers in all the examples so far have acquired latches in a "top-down" manner.

- A worker can only acquire a latch from a node that is below its current node.
- If the desired latch is unavailable, the worker must wait until it becomes available.

But what if workers want to move from one leaf node to another leaf node?


LEAF NODE SCAN EXAMPLE #1

T_1 : Find Keys < 4




LEAF NODE SCAN EXAMPLE #1

T_1 : Find Keys < 4




LEAF NODE SCAN EXAMPLE #1

T_1 : Find Keys < 4




LEAF NODE SCAN EXAMPLE #1

T_1 : Find Keys < 4




LEAF NODE SCAN EXAMPLE #1

T_1 : Find Keys < 4



LEAF NODE SCAN EXAMPLE #1


T_1 : Find Keys < 4




LEAF NODE SCAN EXAMPLE #2

T_1 : Find Keys < 4

T_2 : Find Keys > 1




LEAF NODE SCAN EXAMPLE #2



T_1 : Find Keys < 4

T_2 : Find Keys > 1

LEAF NODE SCAN EXAMPLE #2




T_1 : Find Keys < 4

T_2 : Find Keys > 1

LEAF NODE SCAN EXAMPLE #2

T_1 : Find Keys < 4


T_2 : Find Keys > 1



LEAF NODE SCAN EXAMPLE #2

T_1 : Find Keys < 4


T_2 : Find Keys > 1



LEAF NODE SCAN EXAMPLE #2

T_1 : Find Keys < 4


T_2 : Find Keys > 1




LEAF NODE SCAN EXAMPLE #2

T_1 : Find Keys < 4

T_2 : Find Keys > 1



LEAF NODE SCAN EXAMPLE #2




T_1 : Find Keys < 4

T_2 : Find Keys > 1

LEAF NODE SCAN EXAMPLE #3

T_1 : Delete 4


T_2 : Find Keys > 1




LEAF NODE SCAN EXAMPLE #3

T_1 : Delete 4

T_2 : Find Keys > 1



LEAF NODE SCAN EXAMPLE #3




T_1 : Delete 4

T_2 : Find Keys > 1

LEAF NODE SCAN EXAMPLE #3

T_1 : Delete 4


T_2 : Find Keys > 1



LEAF NODE SCAN EXAMPLE #3

T_1 : Delete 4


T_2 : Find Keys > 1



LEAF NODE SCAN EXAMPLE #3

T_1 : Delete 4

T_2 : Find Keys > 1



LEAF NODE SCAN EXAMPLE #3

T_1 : Delete 4


T_2 : Find Keys > 1

T_2 Choices?

Wait

 *Kill Ourselves*

Kill Other Worker



LEAF NODE SCANS

Latches do not support deadlock detection or avoidance. The only way we can deal with this problem is through coding discipline.

The leaf node sibling latch acquisition protocol must support a “no-wait” mode.

The DBMS's data structures must cope with failed latch acquisitions.

→ Usually transparent to end-user / application.

B+TREE WRITE OPERATIONS

Each worker keeps of leaf node modifications in its private write-set during an operation.

→ List of node identifiers with keys inserted/deleted.

A worker holds write latches on modified nodes until it finishes that operation.

→ Ensures consistency by never exposing partial updates to other threads.

If a worker cannot acquire a write latch on a node:

→ Rollback modifications found in its write-set.

→ Abort the operation by releasing all latches.

CONCLUSION

Making a data structure thread-safe is notoriously difficult in practice.

We focused on B+Trees, but the same high-level techniques are applicable to other data structures.

NEXT CLASS


We are finally going to discuss how to execute some queries...

PROJECT #2

You will build a thread-safe B+tree backed by your buffer pool manager.

- Page Layout
- Insert/Delete/Find Operations
- Iterator
- Latch Crabbing

We define the API for you.
You need to provide the method implementations.



WARNING:
This is more difficult than Project #1.
Start immediately!

<https://15445.courses.cs.cmu.edu/spring2026/project2>

TASKS

Task #1: Page Layouts

- How each node will store its key/values in a page.
- Leaf nodes include tombstones of deleted keys to delay merges.
- You only need to support unique keys.

Task #2: Operations

- Support point queries (single key).
- Support inserts with node splitting.
- Support removal of keys with sibling stealing + merging.
- Does not need to be thread-safe.

TASKS

Task #3: Index Iterator

- Create a STL iterator for range scans on leaf nodes.
- You only need to support ascending scans.

Task #4: Concurrent Index

- Introduce latch crabbing/coupling protocol to support safe concurrent operations.
- Make sure you have splits / merges working correctly before proceeding with this task.

DEVELOPMENT HINTS

Follow the textbook semantics and algorithms.

Set the page size to be small (e.g., 512B) when you first start so that you can see more splits/merges.

Make sure that you protect the internal B+Tree **root_page_id** member.

EXTRA CREDIT

Gradescope Leaderboard runs your code with a specialized in-memory version of BusTub.

The top 20 fastest implementations in the class will receive extra credit for this assignment.

- **#1**: 50% bonus points
- **#2–10**: 25% bonus points
- **#11–20**: 10% bonus points

You must pass all the test cases to qualify!



PLAGIARISM WARNING



The homework and projects must be your own original work. They are not group assignments.

- You may not copy source code from other people or the web.
- You are allowed to use generative AI tools.

Plagiarism is not tolerated. You will get lit up.

- Please ask instructors (not TAs!) if you are unsure.

See [CMU's Policy on Academic Integrity](#) for additional information.